

*One of the most commonly used housings in the commercial, residential and industrial market for small flow applications are the single cartridge, wide diameter housings that have come to be known as the “Big Blue” style. General Filtration has both 10” and 20” versions of these housing available to suit almost any installation.*

Operating Data 10BB & 20BB	
Max Operating Temperature	125° F (52° C)
Max Operating Pressure	125 psi (8.75 bar)
Maximum Recommended Flow Rate	See below
Materials of Construction:	
Body	FDA grade polypro (blue)
Head	FDA grade polypro (black)
Cover o-ring	EPDM
Connections	
Inlet/Outlet	¾”, 1” or 1 ½” NPTF
Cartridge suitability	4 ½” diameter x 10” or 20” long
Weight Empty	5.5 lbs (2.5 kg) for 10” 8.75 lbs (4 kg) for 20”



- Suitable for almost any standard “Big Blue” sized cartridge (not included)
- In-line NPT connections with clearly marked flow directions for ease of installation
- Includes pressure relief button for safer and simpler cartridge change-out with unit inline

ORDERING INFORMATION		
10	BB	1
Length of cartridge to suit: 10 = 10” 20 = 20”	Big Blue Style Housing	NPT Connection: ¾ = ¾” 1 = 1” 1.5 = 1 ½”

Example: 10BB1 = 1” NPT connection for housing ready to hold 1 @ 10” BB cartridge

